

### AMENDMENTS TO THE CLAIMS

Please add or amend the claims to read as follows, and cancel without prejudice or disclaimer to resubmission in a divisional or continuation application claims indicated as cancelled:

1-4. (Cancelled)

5. **(Currently Amended)** ~~The method of claim 4~~ A method for enhancing wide dynamic range in images, the method comprising:

acquiring at least two images of a scene to be imaged, the images acquired using different exposure times, wherein the acquired images are in JPEG format, the JPEG format including a DCT transform domain;

constructing for a first image of said at least two images an illumination mask comprising a set of weight values distinctively identifying respective areas of pixels of high or low illumination, over-exposed or underexposed with respect to a predetermined threshold illumination value,

assigning one of the weight values to each pixel, whereas other weight values are assigned to other pixels of the other of said at least two images;

using a spatial low-pass filter to smooth border zones between pixels of one weight value and pixels of other weight values, thus assigning pixels in the border zones new weight values in a range between the weight values; and

constructing a combined image in the DCT transform domain using image data of pixels assigned with one weight value of the first image and image data of pixels assigned with other weight values of the other of said at least two images and in pixels corresponding to the border zones using image data from said at least two images proportional to the new weight values, wherein the following relation is used in the constructing the combined image:

$$I_{p,q}^{DCT_{WDR}} = \alpha(I_{DC}^{Long}) * I_{p,q}^{DCT_{Long}} + (1 - \alpha(I_{DC}^{Long})) * I_{p,q}^{DCT_{Short}} \cdot Ratio \quad ,$$

APPLICANT(S): VITSNUDEL, Ilya et al.  
SERIAL NO.: 10/622,355  
FILED: July 17, 2003  
Page 3

where  $I_{DC}^{Long}$  is the DC coefficient of the DCT transform of the relatively longer exposure image,  $\alpha$  is a weight representing the illumination mask, and Ratio is a measure that defines the ~~relation~~ relationship between the images of different ~~exposure~~ exposures, and  $p, q$  are DCT coefficients, and  $*$  represents convolution.

6. (Previously presented) The method of claim 5, wherein only first few DCT coefficients are used in calculating the relationship.

7. (Original) The method of claim 6, wherein  $p=1$  and  $q=1$ .

8-9. (Cancelled)

10. **(Currently Amended)** ~~The method of claim 9~~ A method for enhancing wide dynamic range in images, the method comprising:

acquiring at least two images of a scene to be imaged, the images acquired using different exposure times;

detecting pixels in said at least two images indicative of motion by comparing corresponding image data from said at least two images;

constructing for a first image of said at least two images an illumination mask comprising a set of weight values distinctively identifying respective areas of pixels of high or low illumination, over-exposed or underexposed with respect to a predetermined threshold illumination value,

assigning one of the weight values to each pixel, whereas other weight values are assigned to other pixels of the other of said at least two images;

using a spatial low-pass filter to smooth border zones between pixels of one weight value and pixels of other weight values, thus assigning pixels in the border zones new weight values in a range between the weight values;

APPLICANT(S): VITSNUDEL, Ilya et al.  
SERIAL NO.: 10/622,355  
FILED: July 17, 2003  
Page 4

evaluating image data value for pixels identified as indicative of motion using image data from one of said at least two images, using the image data value in constructing the combined image;

constructing a combined image using image data of pixels assigned with one weight value of the first image and image data of pixels assigned with other weight values of the other of said at least two images and in pixels corresponding to the border zones using image data from said at least two images proportional to the new weight values,

wherein the step of detecting pixels indicative of motion comprises looking for pixels for which the ratio  $I^{Long} / \hat{I}^{Long}$  is beyond a predetermined threshold,  $I^{Long}$  is image data from one of said at least two images which was acquired with longest exposure time, and

$$\hat{I}^{Long} = \begin{cases} I^{Short} \cdot Ratio & \text{where } I^{Short} \cdot Ratio < 255 \\ 255 & \text{else} \end{cases},$$

wherein Ratio is a measure that defines the ~~relation~~ relationship between the images of different exposures.

11-13. (Cancelled)

14. (Previously presented) A method for enhancing wide dynamic range in images, the method comprising:

acquiring at least two images of a scene to be imaged, the images acquired using different exposure times;

constructing for a first image of said at least two images an illumination mask comprising a set of weight values distinctively identifying respective areas of pixels of high or low illumination, over-exposed or underexposed with respect to a predetermined threshold illumination value,

assigning one of the weight values to each pixel, whereas other weight values are assigned to other pixels of the other of said at least two images;

using a low-pass filter to smooth border zones between pixels of one weight value and pixels of other weight values, thus assigning pixels in the border zones new weight values in a range between the weight values; and

constructing a combined image using image data of pixels assigned with one weight value of the first image and image data of pixels assigned with other weight values of the other of said at least two images and in pixels corresponding to the border zones using image data from said at least two images proportional to the new weight values,

wherein the acquired images are in JPEG format, the JPEG format including a DCT transform domain, wherein the step of constructing the combined image is carried out in the DCT transform domain, and wherein the following relationship is used in the constructing the combined image:

$$I_{p,q}^{DCT_{WDR}} = \alpha(I_{DC}^{Long}) * I_{p,q}^{DCT_{Long}} + (1 - \alpha(I_{DC}^{Long})) * I_{p,q}^{DCT_{Short}} \cdot Ratio \quad ,$$

where  $I_{DC}^{Long}$  is the DC coefficient of the DCT transform of the relatively longer exposure image,  $\alpha$  is a weight representing the illumination mask, Ratio is a measure that defines the relationship between the images of different exposure exposures,  $p, q$  are DCT coefficients, and  $*$  represents convolution.

15. (Previously presented) The method of claim 14, wherein only first few DCT coefficients are used in calculating the relation.

16. (Previously presented) The method of claim 15, wherein  $p=1$  and  $q=1$ .

17. (Previously presented) The method of claim 14, further comprising:

detecting pixels in said at least two images indicative of motion by comparing corresponding image data from said at least two images; and

evaluating image data value for pixels identified as indicative of motion using image data from one of said at least two images and using the image data value in constructing the combined image.

18. (Previously presented) The method of Claim 17, wherein the step of detecting pixels indicative of motion comprises looking for pixels for which the ratio  $I^{Long} / \hat{I}^{Long}$  is beyond a predetermined threshold,  $I^{Long}$  is image data from one of said at least two images which was acquired with longest exposure time, and

$$\hat{I}^{Long} = \begin{cases} I^{Short} \cdot Ratio & \text{where } I^{Short} \cdot Ratio < 255 \\ 255 & \text{else} \end{cases},$$

wherein Ratio is a measure that defines the relationship between the images of different exposures.

19. (Previously presented) The method of claim 17, wherein the step of constructing a combined image includes using for pixels identified as indicative of motion only image data from one of said at least two images.

20. (Previously presented) The method of claim 19, wherein the image data from one of said at least two images is reconstructed to simulate corresponding pixels in the other of said at least two images.

21. (Previously presented) The method of claim 20, wherein image data from one of said at least two images which was acquired with longest exposure time is incorporated in two illumination masks.